



☐ Order

☐ Quote

Date: _____
Date Requested: _____

LOCATIONS	ASTRAGAL	LOCK/STRIKE			HINGE	MATERIAL		CORE	SEAM
PI PIONEER	FL FLAT - LOOSE	1 - 161	A - ASA	B - SURFACE BOLTS	A1 - 3 1/2	GAUGE	TYPE	HC - HONEYCOMB PI - POLY-INSULATED SS - STEEL STIFFENED SI - SS-INSULATED T - TEMP-RISE* *LIST DEGREE	LS - LOCKSEAM BSL - BONDO-FILLED SEAMLESS WSL - FULL WELD SEAMLESS
	FI FLAT - INSTALLED	2 - 161 DB	D - DEADBOLT STRIKE	C - CONC. VERT. ROD	A2 - 4	0 - 20 GA	A - A40		
	ZL Z - LOOSE	3 - 160	FT - FLUSHBOLT	M - MORT. PANIC	B1 - 4 1/2" SW	8 - 18 GA	B - A60		
	ZI Z - INSTALLED	4 - 86 EDGE	N - NONE	P - PUSH/PULL	B2 - 4 1/2" HW	6 - 16 GA	C - G90		
	N NONE	5 - MORTISE*	T - T-STRIKE	R - RIM PANIC	C1 - 5" SW	4 - 14 GA			
	THICKNESS	6 - 1 1/2" DB	AD - ASA + DEADBOLT	S - SURF. VERT. ROD	C2 - 5" HW	2 - 12 GA			
	4 - 1 3/4	AF - ASA + FLUSHBOLT			* - SEE NOTES				
8 - 1 3/8	O - OTHER (ENTER IN NOTES)								
	BOLD TEXT = STANDARD OPTIONS	* Enter Manufacturer and Model of Mortise Lock in Notes							
* WRITE ON CHART									

[illegible]