



# Acme & Dorf Door

MANUFACTURERS OF HOLLOW METAL DOORS, FRAMES & WOOD DOORS

Phone: (833) 256-2263  
 Fax: (973) 569-9859

Order  
 Quote

Customer: \_\_\_\_\_ PO# \_\_\_\_\_  
 Contact: \_\_\_\_\_ Job Name: \_\_\_\_\_

Date: \_\_\_\_\_  
 Date Requested: \_\_\_\_\_

LINE	QTY	HANDING	MATERIAL	OPENING WIDTH	OPENING HEIGHT	ACTUAL WIDTH	ACTUAL HEIGHT	UNDERCUT	THICKNESS	FIRE LABEL	STYLE	CORE	SEAM	BEVEL	LOCATIONS	HINGES	LOCK/STRIKE	ASTRAGAL	CLOSER REINF. (Y/N)	SEE NOTES	MATY.#	PRICE	
1																							
2																							
3																							
4																							
5																							
6																							
7																							
8																							
9																							
10																							

LOCATIONS	ASTRAGAL	LOCK/STRIKE			HINGE	MATERIAL		CORE	SEAM
AM AMWELD CE CECO CU CURRIES FE FENESTRA ME MESKER NR REPUBLIC (NEW) OR REPUBLIC (OLD) PI PIONEER ST STEELCRAFT * WRITE ON CHART	FL FLAT - LOOSE FI FLAT - INSTALLED ZL Z - LOOSE ZIZ Z - INSTALLED N NONE THICKNESS 4 - 1 3/4 8 - 1 3/8 <b>BOLD TEXT = STANDARD OPTIONS</b>	<b>1 - 161</b> <b>2 - 161 DB</b> 3 - 160 <b>4 - 86 EDGE</b> 5 - MORTISE* 6 - 1 1/2" DB	A - ASA D - DEADBOLT STRIKE FT - FLUSHBOLT N - NONE T - T-STRIKE AD - ASA + DEADBOLT AF - ASA + FLUSHBOLT O - OTHER (ENTER IN NOTES)	B - SURFACE BOLTS C - CONC. VERT. ROD M - MORT. PANIC P - PUSH/PULL R - RIM PANIC S - SURF. VERT. ROD	A1 - 3 1/2 A2 - 4 <b>B1 - 4 1/2" SW</b> B2 - 4 1/2" HW C1 - 5" SW C2 - 5" HW * - SEE NOTES	GAUGE 0 - 20 GA 8 - 18 GA 6 - 16 GA 4 - 14 GA 2 - 12 GA	TYPE A - A40 B - A60 C - G90	HC - HONEYCOMB PI - POLY-INSULATED SS - STEEL STIFFENED SI - SS-INSULATED T - TEMP-RISE* *LIST DEGREE	LS - LOCKSEAM BSL - BONDO-FILLED SEAMLESS WSL - FULL WELD SEAMLESS

